



# Coding for Industry 4.0

#### [Efficient]

Revolutionary printhead, consistent print quality

#### [Reliable]

Stable performance, less maintenance

### [Friendly]

Self-management system, lower makeup consumption









Coding Tomorrow

www.Leadtech-NA.com LEAD TECH-North America





## **Specifications**


| Model                          | <b>i</b> 9 STD   | <b>i9</b> HRS  |
|--------------------------------|--|--|
| Material                       | Precision coating  |  |
| Printing<br>Performance        | 1-4 Lines(7X5matrix)<br>1-5 Lines(5X5 matrix)<br>Max.speed=1128.60ft(344m)/min@5X5   | 1-4 Lines(7X5matrix)<br>1-5 Lines(5X5 matrix)<br>Max.speed=1410.76ft(430m)/min@5X5 |
| Font Matrix                    | Single-Line: 5X5, 7X5, 9x6, 12X8, 16X11, 19X14, 24X17, 32X2<br>Twin-Line: 5X5, 7X5, 9x6, 12X8, 16X11   | 2 3 Lines: 5x5, 7x5, 9x6 5 Lines: 5x5<br>4 Lines: 5x5, 7x5                         |
| Printing Distance              | Character height: 0.04"(1mm) - 0.59"(15mm) Printing distance: 0.08"(2mm) to 1.18"(30mm) Best: 0.39"(10mm)  |  |
| Operating System               | LT-Touch unique System, Multiple Languages   |  |
| Print Content                  | English, Chinese, Arabic Numbers, serial number, Barcode, Shift, DM/QR Code, UPC A&E, EAN 8 &13, Code 128 A, B & C, Code 125, GS1, UCC/EAN 128, Code 39, logo, automatic date/time/expiry date, special characters, etc. |  |
| Extra Memory                   | USB, RS485, RS232, BCD, Ethernet   |  |
| System Language                | Chinese, English, Korean, Russian, Polish, Persian, Arabic, Spanish, German, Indonesian, Vietnamese, Croatian, Thai, Slovenian, Slovak, Bosnian, Portuguese, Italian, etc. customizable language                         |  |
| Memory Storage                 | 1000+Messages  |  |
| Industrial<br>Protection       | IP65   |  |
| Printhead                      | Super soft, length 9.84′(3m)<br>Constant temperature, 60μm   | Super soft, length 9.84'(3m)<br>Constant temperature, 50μm                         |
| Printing Direction             | 360°All-round printing   |  |
| Cartridge<br>Volume            | Ink 0.793 qt. (750ml)<br>Make-up 0.793 qt. (750ml)   |  |
| Temperature/<br>Humidity range | 32-122°F (0 - 50°C)<br>0-95% Relative Humidity, Non-condensing   |  |
| Power                          | AC100-240V, 50/60Hz, 120VA   |  |

<sup>\*</sup> is STD is standard model is HRS is a high-speed, high-resolution, small font model (suitable for applications with high-precision fonts)

## **Dimensions**









#### **LEAD TECH-North America**

Tel: 507-701-6787

Email: Support@LeadTech-NA.com Web: www.LeadTech-NA.com

Address: 300 3rd St SE Ste 6 Rochester MN 55904